

# Mobile Fencing & Security

## Heras EVO Barrier 1.0m Red

### Specifications

Dimensions Height (mm)	555
Dimensions Width (mm)	1000
Dimensions Depth (mm)	400
Package quantity	0
Weight (Kg)	7.00
Weight full	

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



## A fully versatile traffic barrier system

### Create a highly-visible and solid wall with the Heras EVO barriers

The EVO Road Barrier is a fully interlocking barrier system which is produced from UV stabilised prime polyethylene and can be water or sand filled. The barrier is available in three different sizes which can be used together giving a fully versatile traffic barrier system. Creating a continuous solid wall, the barrier can be topped with mesh fencing. It is fully stackable for ease of transport and storage and has been 'Wind Load' tested to resist speeds of up to 55mph.

- Interlocking solid wall barrier system
- Water or sand filled
- Wind loading to 55mph

### Protect members of the public and provide a safe working environment

The guarantees of the Heras traffic demarcation solutions for crowd control. Highly visibility because of the use of safety colours. All Heras traffic demarcation products are clearly visible from afar because of the vibrant red and white safety colours. Used with or without anti-climb panel. Equip your traffic barriers with an anti-climb fence or solid panel to prohibit pedestrians from climbing over it. High-levels of flexibility. Link several units together to create the most suitable traffic demarcation for your building site. Easy handling without crane lifting. After usage, you easily take the barriers with you from site to site without needing a crane to lift them. Wind resistant. As specialists, we can calculate the specific wind resistance for your building site and assist you in choosing the most suitable traffic demarcation products.