

Mobile Fencing & Security

42/60 High Security coupler + Hinge ring

Specifications

Dimensions Height (mm)	55
Dimensions Width (mm)	150
Dimensions Depth (mm)	3
Package quantity	15
Weight (Kg)	0.91

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Fast, safe gate solution for temporary fencing

42/60 High Security coupler for use in semi-permanent set-ups

The 42/60 High Security Heras fence clip has been developed by Heras for use in semi-permanent set-ups. This allows temporary fencing to be attached to posts with Heras fence clips. The High Security Heras fence clip is equipped with nut protection. A high collar prevents the Heras fence clip from being loosened using standard tools. This Heras fence clip can only be (dis)assembled with a specially-developed socket key.

A hinge ring and wheel can be used to make 2 Heras temporary fencing elements function as a swing gate. The metal clamping plates (half moons) are attached to a temporary fencing tube. The Heras temporary fencing can then turn, but is still securely fixed. For this product, the High Security Heras fence clip and hinge ring are welded together. Assembly was never so simple.

- Security in a semi-permanent set-up
- Space saving
- Fast gate solution