

Mobile Fencing & Security

Strut with baseplate

Specifications

Dimensions Height (mm)	1700
Dimensions Width (mm)	150
Dimensions Depth (mm)	150
Package quantity	12
Weight (Kg)	3.50

Disclaimer: There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras.



Limits the risk of Heras mobile fences being blown or knocked over

Limits the risk of Heras mobile fences being blown or knocked over

The Heras fence stabiliser offers improved stability thanks to being fitted at an angle of 45 degrees to the temporary fencing. The Heras fence stabiliser must be fastened to the Heras temporary fencing using a Heras fence clip at a height of approximately 1.8 m. The Heras fence stabilisers are anchored to the ground with a soil pin. If this is not possible, it is possible to place it on the ground and shore it with ballast feet or a Heras fence stabiliser plate. The simple Heras fence stabiliser fitting system ensures a tighter fence line and a professional appearance while making it very difficult to move. An excellent, inexpensive alternative for a semi-permanent set-up. The distance from the fence line to the soil pin is approximately 150 cm. The use of Heras fence stabilisers extends the life of your temporary fencing.

- Professional appearance
- Tight temporary fencing line